

## Features

- Advanced high cell density Trench technology
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- 100% EAS Guaranteed
- Green Device Available


## Product Summary



$V_{DS}$	30	V
$I_D$	9	A
$R_{DS(ON)}$ (at $V_{GS}=10V$ )	12	mΩ
$R_{DS(ON)}$ (at $V_{GS}=4.5V$ )	18	mΩ

## Applications

- High Frequency Point-of-Load, Synchronous Buck Converter for MB/NB/UMPC/VGA
- Networking DC-DC Power System
- Load Switch



## Absolute Maximum Ratings( $T_A=25^\circ C$ , unless otherwise noted)

Parameter	Symbol	Rating	Units
Drain-Source Voltage	$V_{DS}$	30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current, $V_{GS} @ 10V^1$	$I_D @ T_A=25^\circ C$	9	A
Continuous Drain Current, $V_{GS} @ 10V^1$	$I_D @ T_A=70^\circ C$	7	A
Pulsed Drain Current <sup>2</sup>	$I_{DM}$	36	A
Single Pulse Avalanche Energy <sup>3</sup>	EAS	24.2	mJ
Avalanche Current	$I_{AS}$	22	A
Total Power Dissipation <sup>4</sup>	$P_D @ T_A=25^\circ C$	1.5	W
Storage Temperature Range	$T_{STG}$	-55 to 150	°C
Operating Junction Temperature Range	$T_J$	-55 to 150	°C

## Thermal Characteristics

Parameter	Symbol	Typ	Max	Unit
Thermal Resistance Junction-Ambient <sup>1</sup>	$R_{\theta JA}$	---	85	°C/W
Thermal Resistance Junction-Case <sup>1</sup>	$R_{\theta JC}$	---	25	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$ , unless otherwise noted)**

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$V_{\text{GS}}=0\text{V}$ , $I_D=250\mu\text{A}$	30	---	---	V
$\text{BV}_{\text{DSS}}$ Temperature Coefficient	$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	Reference to $25^\circ\text{C}$ , $I_D=1\text{mA}$	---	0.023	---	$\text{V}/^\circ\text{C}$
Static Drain-Source On-Resistance <sup>2</sup>	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=10\text{V}$ , $I_D=8\text{A}$	---	10	12	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}$ , $I_D=6\text{A}$	---	15	18	$\text{m}\Omega$
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{GS}}=V_{\text{DS}}$ , $I_D=250\mu\text{A}$	1.2	---	2.5	V
$V_{\text{GS}(\text{th})}$ Temperature Coefficient	$\Delta V_{\text{GS}(\text{th})}$		---	-5.08	---	$\text{mV}/^\circ\text{C}$
Drain-Source Leakage Current	$I_{\text{DSS}}$	$V_{\text{DS}}=24\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $T_J=25^\circ\text{C}$	---	---	1	$\text{uA}$
		$V_{\text{DS}}=24\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $T_J=55^\circ\text{C}$	---	---	5	
Gate-Source Leakage Current	$I_{\text{GSS}}$	$V_{\text{GS}}=\pm 20\text{V}$ , $V_{\text{DS}}=0\text{V}$	---	---	$\pm 100$	nA
Forward Transconductance	$g_{\text{fs}}$	$V_{\text{DS}}=5\text{V}$ , $I_D=8\text{A}$	---	24	---	S
Gate Resistance	$R_g$	$V_{\text{DS}}=0\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $f=1\text{MHz}$	---	1.8	3	$\Omega$
Total Gate Charge (4.5V)	$Q_g$	$V_{\text{DS}}=15\text{V}$ , $V_{\text{GS}}=4.5\text{V}$ , $I_D=8\text{A}$	---	9.63	---	$\text{nC}$
Gate-Source Charge	$Q_{\text{gs}}$		---	3.88	---	
Gate-Drain Charge	$Q_{\text{gd}}$		---	3.44	---	
Turn-On Delay Time	$T_{\text{d}(\text{on})}$	$V_{\text{DD}}=15\text{V}$ , $V_{\text{GS}}=10\text{V}$ , $R_G=1.5\Omega$ , $I_D=8\text{A}$	---	4.2	---	$\text{ns}$
Rise Time	$T_r$		---	8.2	---	
Turn-Off Delay Time	$T_{\text{d}(\text{off})}$		---	31	---	
Fall Time	$T_f$		---	4	---	
Input Capacitance	$C_{\text{iss}}$	$V_{\text{DS}}=15\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $f=1\text{MHz}$	---	940	---	$\text{pF}$
Output Capacitance	$C_{\text{oss}}$		---	131	---	
Reverse Transfer Capacitance	$C_{\text{rss}}$		---	109	---	


**Drain-Source Diode Characteristics**

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Continuous Source Current <sup>1,5</sup>	$I_s$	$V_G=V_D=0\text{V}$ , Force Current	---	---	9	A
Pulsed Source Current <sup>2,5</sup>	$I_{\text{SM}}$		---	---	36	A
Diode Forward Voltage <sup>2</sup>	$V_{\text{SD}}$	$V_{\text{GS}}=0\text{V}$ , $I_s=1\text{A}$ , $T_J=25^\circ\text{C}$	---	---	1	V
Reverse Recovery Time	$t_{\text{rr}}$	$I_F=8\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$ , $T_J=25^\circ\text{C}$	---	8	---	nS
	$Q_{\text{rr}}$		---	2.9	---	$\text{nC}$


**Note:**

- 1.The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width  $\leq 300\mu\text{s}$  , duty cycle  $\leq 2\%$
- 3.The EAS data shows Max. rating . The test condition is  $V_{\text{DD}}=25\text{V}$ ,  $V_{\text{GS}}=10\text{V}$ ,  $L=0.1\text{mH}$ ,  $I_{\text{AS}}=22\text{A}$
- 4.The power dissipation is limited by  $150^\circ\text{C}$  junction temperature
- 5.The data is theoretically the same as  $I_D$  and  $I_{\text{DM}}$  , in real applications , should be limited by total power dissipation.


## Typical Characteristics




**Fig.1 Typical Output Characteristics**




**Fig.2 On-Resistance vs. G-S Voltage**




**Fig.3 Forward Characteristics of Reverse**








**Fig.4 Gate-Charge Characteristics**




**Fig.5 Normalized  $V_{GS(th)}$  vs.  $T_J$**



**Fig.6 Normalized  $R_{DS(on)}$  vs.  $T_J$**



### SOP-8 Package Outline Dimensions



Symbol	Dimensions (unit:mm)			Symbol	Dimensions (unit:mm)		
	Min	Typ	Max		Min	Typ	Max
<b>A</b>	1.35	1.55	1.75	<b>A<sub>1</sub></b>	0.10	0.18	0.25
<b>A<sub>2</sub></b>	1.25	1.45	1.65	<b>A<sub>3</sub></b>	--	0.25	--
<b>b<sub>p</sub></b>	0.36	0.42	0.51	<b>c</b>	0.19	0.22	0.25
<b>D</b>	4.70	4.92	5.10	<b>E</b>	3.80	3.90	4.00
<b>e</b>	--	1.27	--	<b>H<sub>E</sub></b>	5.80	6.00	6.20
<b>L</b>	--	1.05	--	<b>L<sub>P</sub></b>	0.40	0.68	1.00
<b>Q</b>	0.60	0.65	0.73	<b>v</b>	--	0.25	--
<b>w</b>	--	0.25	--	<b>y</b>	--	0.10	--
<b>Z</b>	0.30	0.50	0.70	<b>θ</b>	0°		8°