

Features

- Low drain-source on-resistance: $R_{DS(ON)}=0.32\Omega(\text{typ})$
- Easy to control gate switching
- Enhancement mode: $V_{th} = 3.0$ to $4.0V$
- 100% avalanche tested
- RoHS compliant


Key Performance Parameters



| Parameter | Value | Unit |
|----------------------|-------|------------|
| $V_{DS} @ T_{j,max}$ | 600 | V |
| $R_{DS(ON),max}$ | 370 | m Ω |
| I_D | 11 | A |
| $Q_{g,typ}$ | 20 | nC |
| I_{DM} | 30 | A |

Applications

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- Charger, Lighting



Absolute Maximum Ratings ($T_C=25^\circ\text{C}$, unless otherwise noted)

| Parameter | Symbol | TO-252/TO-220 | TO-220F | Unit |
|---|-----------|---------------|---------|------------------|
| Drain-Source Voltage | V_{DS} | 600 | | V |
| Gate-Source Voltage | V_{GS} | ± 30 | | V |
| Continuous Drain Current ¹ | I_D | 11 | | A |
| Pulsed Drain Current ² | I_{DM} | 30 | | A |
| Single Pulse Avalanche Energy ⁴ | EAS | 320 | | mJ |
| Avalanche Current | I_{AS} | 4 | | A |
| Repetitive Avalanche energy, t_{AR} limited by $T_{j,max}$ | E_{AR} | 0.4 | | mJ |
| MOSFET dv/dt ruggedness, $V_{DS} = 0 \dots 400V$ | dv/dt | 50 | | V/ns |
| Reverse diode dv/dt ³ $V_{DS}=0 \dots 400V, I_{sp} \leq I_D$ | | 50 | | |
| Total Power Dissipation ($T_C=25^\circ\text{C}$) | P_D | 78 | 31 | W |
| Storage Temperature Range | T_{STG} | -55 to 150 | | $^\circ\text{C}$ |
| Operating Junction Temperature Range | T_J | -55 to 150 | | $^\circ\text{C}$ |

Thermal Characteristics

| Parameter | Symbol | TO-252/TO-220 | TO-220F | Unit |
|-------------------------------------|-----------------|---------------|---------|--------------------|
| Thermal Resistance Junction-Ambient | $R_{\theta JA}$ | 62 | 80 | $^\circ\text{C/W}$ |
| Thermal Resistance Junction-Case | $R_{\theta JC}$ | 1.6 | 4 | $^\circ\text{C/W}$ |

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|-----------------------------------|--------------|--|-----|-----|-----------|------------|
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V, I_D=250\mu A$ | 600 | --- | --- | V |
| Static Drain-Source On-Resistance | $R_{DS(ON)}$ | $V_{GS}=10V, I_D=5.5A$ | --- | 320 | 370 | m Ω |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{GS}=V_{DS}, I_D=250\mu A$ | 3.0 | --- | 4.0 | V |
| Drain-Source Leakage Current | I_{DSS} | $V_{DS}=600V, V_{GS}=0V, T_J=25^\circ\text{C}$ | --- | --- | 1 | uA |
| | | $V_{DS}=600V, V_{GS}=0V, T_J=150^\circ\text{C}$ | --- | --- | 100 | |
| Gate-Source Leakage Current | I_{GSS} | $V_{GS}=\pm 30V, V_{DS}=0V$ | --- | --- | ± 100 | nA |
| Gate Resistance | R_G | $f = 1.0\text{MHz}$, open drain | --- | 14 | --- | Ω |
| Total Gate Charge | Q_g | $V_{DD}=400V, V_{GS}=10V, I_D=11A$ | --- | 20 | --- | nC |
| Gate-Source Charge | Q_{gs} | | --- | 4.2 | --- | |
| Gate-Drain Charge | Q_{gd} | | --- | 7 | --- | |
| Turn-On Delay Time | $T_{d(on)}$ | $V_{DD}=400V, V_{GS}=10V, R_G=25\Omega, I_D=11A$ | --- | 41 | --- | ns |
| Rise Time | T_r | | --- | 20 | --- | |
| Turn-Off Delay Time | $T_{d(off)}$ | | --- | 120 | --- | |
| Fall Time | T_f | | --- | 20 | --- | |
| Input Capacitance | C_{iss} | $V_{DS}=100V, V_{GS}=0V, f=1\text{MHz}$ | --- | 797 | --- | pF |
| Output Capacitance | C_{oss} | | --- | 30 | --- | |
| Reverse Transfer Capacitance | C_{rss} | | --- | 4.2 | --- | |

Drain-Source Diode Characteristics

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|-------------------------------|-----------|---|-----|-----|-----|------|
| Continuous Source Current | I_S | $T_C=25^\circ\text{C}$ | --- | --- | 11 | A |
| Pulsed Source Current | I_{SM} | | --- | --- | 30 | A |
| Diode Forward Voltage | V_{SD} | $V_G=0V, I_S=11A, T_J=25^\circ\text{C}$ | --- | 0.9 | 1.2 | V |
| Reverse Recovery Time | t_{rr} | $V_R=400V, I_F=11A, di_F/dt=100A/\mu s$ | --- | 330 | --- | ns |
| Reverse Recovery Charge | Q_{rr} | | --- | 3.5 | --- | uC |
| Peak Reverse Recovery Current | I_{rrm} | | --- | 22 | --- | A |

Note:

- Limited by $T_{J,max}$. Maximum Duty Cycle $D = 0.50$
- Pulse width t_p limited by $T_{J,max}$
- Identical low side and high side switch with identical R_G
- $V_{DD}=50V, R_G=25\Omega, I_{AS}=4A$

Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 4. Capacitance




Figure 5. Gate Charge




Figure 6. Body Diode Forward Voltage




Figure 7. On-Resistance vs. Junction Temperature




Figure 8. Threshold Voltage vs. Junction Temperature




Figure 9. Transient Thermal Impedance TO-252, TO-220






Figure 10. Transient Thermal Impedance TO-220F

TO-252 Package Outline Dimensions




| Symbol | Dimensions (unit:mm) | | | Symbol | Dimensions (unit:mm) | | |
|----------------------|----------------------|-------|-------|----------------------|----------------------|-------|-------|
| | Min | Typ | Max | | Min | Typ | Max |
| A | 2.20 | 2.30 | 2.38 | E₁ | 4.40 | -- | -- |
| A₁ | 0.46 | 0.50 | 0.63 | e | 2.286 BSC | | |
| b | 0.64 | 0.76 | 0.89 | e₁ | -- | 4.57 | -- |
| b₁ | 0.77 | 0.85 | 1.14 | H_D | 9.40 | 10.00 | 10.40 |
| b₂ | 5.00 | 5.33 | 5.46 | L | 2.743 REF | | |
| c | 0.458 | 0.508 | 0.558 | L₁ | 1.40 | 1.52 | 1.77 |
| D₁ | 5.98 | 6.10 | 6.223 | L₂ | 0.50 | 0.80 | 1.01 |
| D₂ | 5.21 | -- | -- | W | -- | 0.20 | -- |
| E | 6.40 | 6.60 | 6.731 | y | -- | -- | 0.20 |

TO-220 Package Outline Dimensions



| Symbol | Dimensions (unit:mm) | | | Symbol | Dimensions (unit:mm) | | |
|-----------|----------------------|-------|-------|--------------|----------------------|-------|-------|
| | Min | Typ | Max | | Min | Typ | Max |
| A | 4.30 | 4.55 | 4.75 | E | 9.65 | 10.00 | 10.25 |
| A1 | 1.15 | 1.30 | 1.45 | E3 | 7.00 | -- | -- |
| A2 | 2.20 | 2.40 | 2.60 | e | 2.54 BSC | | |
| b | 0.70 | 0.80 | 0.95 | e1 | 5.08 BSC | | |
| b2 | 1.17 | 1.27 | 1.47 | H1 | 6.30 | 6.50 | 6.80 |
| c | 0.40 | 0.50 | 0.65 | L | 12.70 | 13.50 | 14.10 |
| D | 15.30 | 15.60 | 15.90 | L1 | -- | 3.20 | 3.95 |
| D1 | 8.90 | 9.10 | 9.35 | phi P | 3.40 | 3.60 | 3.80 |
| D2 | 5.50 | -- | -- | Q | 2.60 | 2.80 | 3.00 |

TO-220F Package Outline Dimensions



| Symbol | Dimensions (unit:mm) | | | Symbol | Dimensions (unit:mm) | | |
|-----------|----------------------|-------|-------|---------------|----------------------|-------|-------|
| | Min | Typ | Max | | Min | Typ | Max |
| A | 4.40 | 4.70 | 5.00 | H1 | 6.70 REF | | |
| A1 | 2.30 | 2.55 | 2.80 | L | 12.30 | 12.98 | 13.30 |
| A2 | 0.30 | 0.50 | 0.70 | L1 | 2.95 | 3.10 | 3.50 |
| A4 | 2.45 | 2.80 | 3.05 | phi P | 3.03 | 3.20 | 3.50 |
| c | 0.30 | 0.50 | 0.70 | phi P3 | 3.15 | 3.45 | 3.65 |
| c1 | 1.20 | 1.30 | 1.40 | b1 | 1.10 | 1.30 | 1.45 |
| D | 15.40 | 15.90 | 16.40 | b2 | 0.60 | 0.80 | 1.00 |
| E | 9.86 | 10.16 | 10.46 | F3 | 3.05 | 3.30 | 3.55 |
| e | 2.54 BSC | | | G3 | 1.15 | 1.35 | 1.55 |