

Features

- Advanced high cell density Trench technology
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- Green Device Available


Product Summary



V_{DS}	20	V
I_D	6	A
$R_{DS(ON)}$ (at $V_{GS}=4.5V$)	28	mΩ
$R_{DS(ON)}$ (at $V_{GS}=2.5V$)	37	mΩ

Applications

- High Frequency Point-of-Load,Synchronous Buck Converter
- Networking DC-DC Power System
- Load Switch



Absolute Maximum Ratings($T_A=25^\circ C$, unless otherwise noted)

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	± 10	V
Continuous Drain Current ¹	I_D	6	A
Continuous Drain Current ¹	$I_D @ T_C = 100^\circ C$	3.8	A
Pulsed Drain Current ²	I_{DM}	25	A
Total Power Dissipation ³	P_D	1.25	W
Storage Temperature Range	T_{STG}	-55 to 150	°C
Operating Junction Temperature Range	T_J	-55 to 150	°C

Thermal Characteristics

Parameter	Symbol	Typ	Max	Unit
Thermal Resistance Junction-Ambient ¹	$R_{\theta JA}$	---	100	°C/W

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}}=0\text{V}$, $I_D=250\mu\text{A}$	20	---	---	V
Static Drain-Source On-Resistance	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=4.5\text{V}$, $I_D=6\text{A}$	---	20	28	$\text{m}\Omega$
		$V_{\text{GS}}=2.5\text{V}$, $I_D=5\text{A}$	---	26	37	$\text{m}\Omega$
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{GS}}=V_{\text{DS}}$, $I_D=250\mu\text{A}$	0.5	0.7	1.2	V
Drain-Source Leakage Current	I_{DSS}	$V_{\text{DS}}=20\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=25^\circ\text{C}$	---	---	1	μA
Gate-Source Leakage Current	I_{GSS}	$V_{\text{GS}}=\pm 10\text{V}$, $V_{\text{DS}}=0\text{V}$	---	---	± 100	nA
Forward Transconductance	g_{fs}	$V_{\text{DS}}=5\text{V}$, $I_D=6\text{A}$	20	---	---	S
Total Gate Charge	Q_g	$V_{\text{DS}}=10\text{V}$, $V_{\text{GS}}=4.5\text{V}$, $I_D=3\text{A}$	---	10	---	nC
Gate-Source Charge	Q_{gs}		---	1.5	---	
Gate-Drain Charge	Q_{gd}		---	1.6	---	
Turn-On Delay Time	$T_{\text{d}(\text{on})}$	$V_{\text{DD}}=10\text{V}$, $R_G=6\Omega$, $V_{\text{GS}}=4.5\text{V}$, $I_D=1\text{A}$	---	8	---	ns
Rise Time	T_r		---	9	---	
Turn-Off Delay Time	$T_{\text{d}(\text{off})}$		---	15	---	
Fall Time	T_f		---	4	---	
Input Capacitance	C_{iss}	$V_{\text{DS}}=10\text{V}$, $V_{\text{GS}}=0\text{V}$, $f=1\text{MHz}$	---	640	---	pF
Output Capacitance	C_{oss}		---	140	---	
Reverse Transfer Capacitance	C_{rss}		---	80	---	

Drain-Source Diode Characteristics

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Continuous Source Current ²	I_s		---	---	6	A
Diode Forward Voltage ¹	V_{SD}	$V_{\text{GS}}=0\text{V}$, $I_s=1.7\text{A}$, $T_J=25^\circ\text{C}$	---	---	1.2	V

Note:

- 1.The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$
- 3.The power dissipation is limited by 150°C junction temperature

Typical Characteristics




Figure 1 Output Characteristics




Figure 2 Transfer Characteristics




Figure 3 Rdson- Drain Current




Figure 4 Rdson-JunctionTemperature




Figure 5 Gate Charge




Figure 6 Source- Drain Diode Forward




Figure 7 Capacitance vs Vds




Figure 8 Safe Operation Area




Figure 9 BV_{DSS} vs Junction Temperature




Figure 10 $V_{GS(th)}$ vs Junction Temperature





Figure 11 Normalized Maximum Transient Thermal Impedance

SOP-8 Package Outline Dimensions



Symbol	Dimensions (unit:mm)			Symbol	Dimensions (unit:mm)		
	Min	Typ	Max		Min	Typ	Max
A	1.35	1.55	1.75	A₁	0.10	0.18	0.25
A₂	1.25	1.45	1.65	A₃	--	0.25	--
b_p	0.36	0.42	0.51	c	0.19	0.22	0.25
D	4.70	4.92	5.10	E	3.80	3.90	4.00
e	--	1.27	--	H_E	5.80	6.00	6.20
L	--	1.05	--	L_p	0.40	0.68	1.00
Q	0.60	0.65	0.73	v	--	0.25	--
w	--	0.25	--	y	--	0.10	--
Z	0.30	0.50	0.70	θ	0°		8°